



Elegant Design  
 High Performance  
 Flexible Ergonomics

The POS-510 EyePOS GT II has the character of a stylish sports car. Just like the POS-500 EyePOS II, it is a POS system with the glass-metal stand engineered by 4POS that shines without and convinces within. New with increased graphics/processor performance and USB3.0. With this model, 4POS has developed a compact all-in-one POS solution absolutely matchless in design. The POS terminal can be used freestanding on the counter, fixed at the checkout, mounted on the wall – it really couldn't be more flexible.



# Touch System POS-500 EyePOS II POS-510 EyePOS GT II



1. Bezel-free touch



2. Stand in metal-glass-construction




3. 8.4" stand alone customer display



4. VFD stand alone customer display



5. 8.4" rear mount customer display



6. Rich I/O connector ports  
 - 5 x USB 2.0  
 - up to 2 x USB 3.0

# POS-500 EyePOS II POS-510 EyePOS GT II



| Model Name                   | POS-500 EyePOS II   | POS-510 EyePOS GT II  |
|------------------------------|---|---|
| <b>Housing</b>               |   |   |
| Mount                        | Die Cast Magnesium-Aluminium<br>VESA 100  |   |
| <b>Mainboard</b>             |   |   |
|                              | D36   | D66   |
| CPU                          | Intel Celeron J1900 2.0GHz (fanless)  | Intel Celeron G1820TE 2.2GHz /<br>Intel Core i5-4590T 2.0/3.0GHz                |
| Chipset / GPU                | Intel HD Graphics   | Intel Q87 PCH (AMT/RAID enabled) /<br>Intel HD Graphics                         |
| System Memory                | 1 x DDR3L-1600 SO-DIMM up to 8GB  |   |
| <b>Display / Touch</b>       |   |   |
| Display Size                 | 15" TFT LCD with LED backlight  |   |
| Brightness                   | 250 cd/m <sup>2</sup>   |   |
| Maximum Resolution           | 1024 x 768  |   |
| Touch Screen Type            | Resistive or Capacitive   |   |
| Tilt Angle (Degree)          | 30° Low Stand / 70° High Stand  |   |
| <b>Storage</b>               |   |   |
| Primary Device Bay           | 1 x 2.5 SATA (HDD or SSD)   |   |
| Flash Memory                 | 1 x mSATA SSD   |   |
| <b>External I/O Ports</b>    |   |   |
| USB                          | 6 x USB (5 x USB 2.0 + 1 x USB 3.0)   | 7 x USB (5 x USB 2.0 + 2 x USB 3.0)   |
| Parallel Port                | N/A   |   |
| Serial/COM                   | 3 x COM ports with RJ-45 (5V/12 power selectable by BIOS) +<br>1 x COM with DB9 | 3 x COM ports with RJ-45 (5V/12 power selectable by BIOS) +<br>1 x COM with DB9 |
| LAN                          | 1 x RJ-45 (10/100/1000 Mbit)  |   |
| VGA out                      | 1 x D-Sub (15 pin) with Power over VGA (activated via BIOS)                     |   |
| Cash Drawer                  | 1 x RJ-11 with 12V or 19V   |   |
| Speaker                      | 2 x 2W  |   |
| Audio                        | 1 x Line-out  |   |
| <b>Control/Indicator</b>     |   |   |
| Power Button                 | 1 with Power LED  |   |
| Power Supply                 | External 65W/19V  | External 120W/19V   |
| <b>Environment</b>           |   |   |
| EMC & Safety                 | FCC, Class A, CE, LVD   |   |
| Operating Temperature        | 5° C ~ 35° C  |   |
| IP                           | IP65 sealed front panel with touch screen                                       |   |
| <b>Options</b>               |   |   |
| Second Display               | 8.4" TFT LCD / VFD Display (2x20, 5mm character)                                |   |
| WLAN                         | 802.11 a/b/g mini PCI-E Wireless LAN Card                                       |   |
| Magnetic Card Reader         | 3 Tracks MSR (via USB)  |   |
| <b>Dimension (W x D x H)</b> |   |   |
| Low Stand                    | 360 x 275 x 173 mm  |   |
| High Stand                   | 360 x 228 x 283 mm  |   |
| <b>Weight</b>                |   |   |
|                              | 4.8 kg  | 5.1 kg  |
| <b>Colour</b>                |   |   |
|                              | Black or Glossy white   |   |
| <b>OS Support</b>            |   |   |
|                              | Windows 7, POSReady 7, Windows 8.1, Linux                                       |   |

Notes: Specifications are subject to change without notice. Product photos and pictures are for illustration purposes only and may differ from the real product's appearance.

V1502